



Specifications

Model	DYD-E10B	DYD-E12B	DYD-F20A	DYD-F25A
Power Supply	220-240V~ 50Hz	220-240V~ 50Hz	220-240V~ 50Hz	220-240V~ 50Hz
Dehumidifying Capacity	10L/day(30°C RH80%) 5.5L/day(27°C RH60%)	12L/day(30°C RH80%) 7L/day(27°C RH60%)	20L/day(30°C RH80%) 12L/day(27°C RH60%)	25L/day(30°C RH80%) 14.6L/day(27°C RH60%)
Power	155W	175W	320W	390W
Air Volume	- High 90m³/h - Low /	95m³/h /	135m³/h /	155m³/h /
Noise Level	- High 41dB(A) - Low /	43dB(A) /	46dB(A) 44dB(A)	46dB(A) /
Water Tank	2.5L	2.5L	5.5L	5.5L
Operating Temperature	5~35°C	5~35°C	5~35°C	5~35°C
Refrigerant	R134a	R134a	R134a	R410A
Net Weight	10.4 kg	11.0 kg	13.2 kg	14.2 kg
Gross Weight	11.5 kg	12.1 kg	14.6 kg	15.6 kg
Product Size(W × D × H)	325 × 248 × 475 mm	325 × 248 × 475 mm	385 × 290 × 595 mm	385 × 290 × 595 mm
Packing Size(W × D × H)	360 × 295 × 525 mm	360 × 295 × 525 mm	415 × 325 × 660 mm	415 × 325 × 660 mm
Loading Quantity	20'GP 484pcs 40'GP 992pcs 40'HQ 1,230pcs	484pcs 992pcs 1,230pcs	294pcs 588pcs 784pcs	294pcs 588pcs 784pcs

Features

- Auto Dehumidifying
- 24 Hours Timer - off
- LED Display + Soft Buttons
- Safety Child Lock
- Convenient Cord Bracket

Accessory Selectable

- 10mm HEPA Filter
- 10mm Carbon Filter
- Drainage Pipe 30cm / 60cm / Customized

Certification Programs

CB, RoHS Approved by BV / TUV Rheinland

* Different control types (LCD + Touch Panel) and different top cover designs selectable.

